

## DCU 208 Engine Control Unit

Part#: 1006480

Rev. October 2015

### Interfaces

Section	Ch.	Cond.	Min	Typ	Max	Unit	Comment
Power Supply	1		8	12/24	32	VDC	
Digital Input	10	low=0-2 high=8-32	-	12/24	-	VDC	
4-20 mA Input	2		0	4-20	25	mA	Accuracy: +/- 0.5 % of range
PT100 Input	2		0	-	800	C	Accuracy: +/- 2.0 % of range
Digital Output	6		Vin-0.5	Vin-0.3	Vin-0.2	V	Ch. 1-2: 0.5 A fuse Ch. 3-6: 0.2 A fuse
Relay Output	3		0	-	1	A	1 alarm , 2 configurable, potential free, 1A fuse on common
Tacho	1		0.1 4		10 32	kHz Vpp	Magnetic pickup
CAN J1939	1		-	250	-	kbps	SAE J1939
Ethernet	1		-	100	-	Mbps	
Modbus TCP	1		-	100	-	Mbps	
Modbus RTU	1		-	19 200	-	baud	
RIO Link Expansion	1		-	19 200	-	baud	Max one RIO 410 and one RIO 425
USB Port	1		-	-	-	-	USB 1.1 Memory Interface

### Size and Weight

Section	Weight	Width	Height	Depth	Unit	Comment
Size	-	161	132	37	mm	
Weight	340	-	-	-	g	

### Environmental

Section	Condition	Min	Typ	Max	Unit	Comment
Vibration	Operational	-	0.7	-	g	IEC 60068-2-6 Fc
Dry Heat	Operational	-	-	70 16	C hours	IEC 60068-2-2 Bb/Bd
Damp Heat, cyclic	Cyclic 20-55-20 Humidity 95 % Duration	- - -	- - -	- - 48	C - hours	IEC 60068-2-30 Db
Operating Temperature	Operational	5	-	70	C	IEC 60068-2-1 Ab/Ad
Storage Temperature	Not powered	-30	-	+80	C	
Enclosure	Operational	-	IP44	-	-	Front panel
High Voltage	Not powered	-	-	548 1	Vrms minute	Voltage applied between <i>clamped</i> supply and shield.
Fast low-energy Transients/bursts	Operational	-	-	- 2 1	- kV kV	IEC 61000-4-4 24 VDC supply lines, 5kHz Signal lines, 5kHz
Slow high-energy Transients/surges	Operational	-	-	- 0.5 1	- kV kV	IEC 61000-4-5 24 VDC supply lines Signal lines
Electrostatic Discharge, ESD	Operational	8 6	- -	- 8 6	- kV kV	IEC 61000-4-2 Air Contact

## DCU 208 Engine Control Unit

Part#: 1006480

Rev. October 2015

### EMC

Section	Condition	Min	Typ	Max	Unit	Comment
Conducted emission	Operational	-	-	-	-	CISPR 16-1-1 / 16-1-2 / 16-2-1
						Quasi-peak at 3m:
		150	-	300	kHz	80-50 dB $\mu$ V/m
Radiated emission	Operational	0.3	-	300	MHz	50-34 dB $\mu$ V/m
		30	-	156	MHz	54 dB $\mu$ V/m
		156	-	165	MHz	24 dB $\mu$ V/m
		165	-	2 000	MHz	54 dB $\mu$ V/m
Radio frequency Immunity	Operational	-	-	10	Vrms	IEC 61000-4-6
Radiated electric Immunity	Operational	80	-	2 000	MHz	IEC 61000-4-3 10 V/m, 80 % AM, 1 kHz

#### Validity of Information

Data valid at revision date. Auto-Maskin reserves the right to make improvements and changes of specification at any time.

Created by:



Svein Arild Hagnæss, Marine Dept.

Checked by:



Jonas Kjærnli, Marine Dept.