

## Marine Watch S-Series Broadcast Cabinet

Part# 2500230

Rev. February 2022

### Interfaces

Section	Ch.	Cond.	Min	Typ.	Max	Unit	Comment
Power Supply	1	@ 24 VDC	14 0.5	24 1.5	31 4	VDC A	Max ripple is 10% without exceeding Min and Max values.
Ethernet	4	-	-	10 / 100	-	Mbps	
Antenna <sup>1</sup>	1	-	-	-	-	-	0.5 m or 5 m antenna cable options available

### Measurements and Weight

Section	Weight	Width	Height	Depth	Unit	Comment
Size	-	300	300	210	mm	
Weight	8	-	-	-	kg	

### Operator Interface

- Power switch
- GSM connection indicator lamp

### Environmental

Section	Condition	Min.	Typ.	Max.	Unit	Comment
Operating Temperature	Operational	-25	-	+60	°C	
Storage Temperature	Not powered	-40	-	+85	°C	
Enclosure Ingress Protection Rating	Operational	IP66	-	-	-	
Vibration	Operational	-	5	-	g	IEC 60068-2-6 Fc

#### Validity of Information

Data valid at revision date. Auto-Maskin reserves the right to make improvements and changes of specification at any time.

<sup>1</sup> Make sure that the placement of the antenna does not interfere with any other electronic equipment.